



Glenair IPT and IPT-SE Series MIL-DTL-26482 Serie I Bayonet Connectors Summary of Connector Styles and Backshells

Glenair IPT and IPT SE series connectors offer rugged, high vibration performance and rapid mating for both high-performance and general duty signal connector applications. The products are environmentally sealed and can be equipped with EMI/RFI shield termination backshell accessories. IPT SE is qualified to VG 95328. Both product series are in accordance with MIL-DTL-26482 Serie I.

IPT-SE AND IPT PRODUCT FEATURES AND SPECIFICATIONS

Feature	Description
Applications	Factory equipment, off-road vehicles, military vehicles, sensors, power generators, and other industrial applications.
Shell Construction	Aluminum shell bodies provide durable performance in a lightweight package.
Mating System	Three pin bayonet system, 1/2 turn to full mate.
Shell Surface Coatings	A range of conductive and non-conductive surface coatings including standard Cadmium finishes as well as RoHS compliant electrostatic paint.
Environmental Sealing	Individual wire sealing grommets and optional environmental backshells provide moisture protection up to IP67.
Temperature Tolerance	F6, F7, F11 and G3 plated connectors are tested to -55°C to 125°C.
Contacts	High performance crimp contacts and retention clips (IPT SE) and general duty crimp and solder contacts (IPT).
Contact Plating	Copper alloy with gold plating.
Wire Gauge	Contacts support wire sizes #12 - #14 (Size 12), #16 - #20 gauge (Size 16) and #20 - #24 (size 20).
Insert Materials	Resilient high-insulation synthetic insert (polychloroprene or silicone). IPT SE version includes hard plastic retention clip retainer.
Insert Arrangements	IPT SE: 25 different power and signal insert arrangements, featuring 16 and 20 gauge contacts; 3 to 61 contacts. IPT: 39 different power and signal insert arrangements, featuring 12, 16 and 20 gauge contacts; 2 to 61 contacts.
EMI Shielding	Shield termination backshell accessories are available for all plug and receptacle configurations.
Shell Styles	Complete range of shell styles is available, including front and rear mount flange receptacles, jam nut receptacles, bulkhead feedthrus, and straight and 90° plugs.
Polarization	5 keyway configuration with optional polarization.
Approvals	IPT SE is qualified to VG 95328. Both IPT and IPT SE meet all requirements of MIL-DTL-26482 Serie I.
Intermateability	Intermateable with all industry standard bayonet connectors designed to MIL-DTL-26482 Serie I and VG 95328 including Veam VPT, Amphenol PT and ITT Cannon KPT.