

# SPRING ACTION ProSeal™ environmental connector covers



## IP ratings

ProSeal Part Number	Dust-Tight No Ingress of Dust with Underpressure	Water Resistant Shower Spray at 200 mm	Water Resistant Nozzle Ø6.3 mm At 2.5 m	Water Resistant Nozzle Ø12.5 mm At 2.5 m	Water Proof Immersion Tank At 1.0 m for 30 min.	Water Proof Immersion Tank at 10.0 m for 30 min.	Water Proof Random Vibration with Shower
IP Rating	IP6X	IPX4	IPX5	IPX6	IPX7	IPX8	N/A
667-450	✓	✓	✓	✓	✓	✓	✓
667-451	✓	✓			✓		
667-488	✓	✓			✓		
667-472	✓	✓			✓		
667-467	✓	✓			✓		
667-447	✓	✓			✓		
667-448	✓	✓	✓	✓	✓	✓	✓
667-449	✓	✓			✓		
667-497	✓	✓			✓		
667-509	✓	✓	✓	✓	✓	✓	✓
667-387	✓	✓			✓		
667-392	✓	✓			✓		
667-424	✓	✓			✓		
667-462	✓	✓	✓	✓	✓	✓	✓
667-511	✓	✓			✓		
667-512	✓	✓	✓	✓	✓	✓	✓
667-466	✓	✓			✓		
667-479	✓	✓			✓		
667-486	✓	✓			✓		
667-513	✓	✓			✓		
667-431	✓	✓			✓		

\* Connector-dependent (potted connector)