

Series 66 Protective Covers

for Series 801 Mighty Mouse Connectors

667-217 Plug Cover

MM801 Plug Cover



667-217 protective cover fits Glenair Series 801 plug connectors. Aluminum or stainless steel, with stainless steel fittings. Fluorosilicone gasket.

TABLE 1 MATERIAL / FINISH

Aluminum	Stainless Steel
-C Black Anodize	-Z1 Passivate
-M Electroless Nickel	
-NF Olive Drab Cadmium	
-MT Nickel-PTFE	
-ZR Black Zinc-Nickel	
-TZ Tin-Zinc	

TABLE 2 ATTACHMENT TYPE

D		SST Bead Chain .125 (3.2) diameter, size 6, -65 to +200 °C
F		Wire Rope, Blue Nylon Jacket 6/6 nylon over stainless steel rope, fair flexibility, good abrasion resistance, -55 to +100 °C
G		Black Nylon Rope Very flexible, good abrasion and fuel resistance, .094 (2.4) diameter, -55 to +100 °C
H		Wire Rope, Clear FEP Jacket Clear FEP jacket over SST rope, fair flexibility, good abrasion resistance, .100" diameter, -65 to +200 °C
S		Sash Chain #8 sash chain, stainless steel. Length tolerance is ± one link. .280 (Z1)
SK		Nylon Rope with Slip Knot Very flexible, good abrasion and fuel resistance, .094 (2.4) diameter. Length includes .5" (13mm) dia. loop, -55 to +100 °C
T		SST Wire Rope, No Jacket Good flexibility, good abrasion resistance, .047 (1.2) diameter, passivated, -65 to +200 °C
U		Wire Rope, Black Polyurethane Stainless steel rope with black polyurethane coating, flexible, excellent abrasion resistance and resistance to fuels, .080" (2mm) diameter, -55 to +125 °C

PART NUMBER

	667-217	-M	-H	17	17	-5
Base P/N	667-217					
Material/Finish	See Table 1					
Attachment Type	-N No Attachment See Table 2 for Attachment Types					
Shell Size	5 6 7 8 9 10 11 13 16 17 19 21					
Attachment Ring	Omit for Attachment Types N and SK -00 No Ring See Table 3 for Attachment Ring Codes					
Attachment Length	Omit for Attachment Type N Length in One Inch Increments					

Shell Size	A Thread	ø C Max In.	ø C Max mm.
5	.3125-.05P-1L-2A	.465	11.8
6	.375-.05P-1L-2A	.525	13.3
7	.4375-.05P-1L-2A	.590	14.9
8	.5000-.05P-1L-2A	.653	16.6
9	.5625-.05P-1L-2A	.715	18.0
10	.6250-.05P-1L-2A	.778	19.7
11	.6875-.05P-1L-2A	.840	21.3
13	.8125-1P-2L-2A	.965	24.4
16	1.000-1P-2L-2A	1.150	29.2
17	1.062-1P-2L-2A	1.215	30.8
19	1.1875-1P-2L-2A	1.340	34.0
21	1.3125-1P-2L-2A	1.477	37.5




TABLE 3 ATTACHMENT RING

EYELET		SOLID RING		SPLIT RING		CABLE TIE	
Code	Eyelet I.D.	Code	Ring I.D.	Code	Ring I.D.	Code	WS
01	.125 (3.2)	32	.265 (6.7)	19	.885 (22.5)	50	.432 (11.0)
02	.145 (3.7)	29	.315 (8.0)	26	.950 (24.1)	52	.492 (12.5)
04	.182 (4.6)	14	.385 (9.8)	28	1.015 (25.8)	54	.648 (16.5)
06	.197 (5.0)	15	.445 (11.3)	20	1.070 (27.2)	56	.757 (19.2)
		33	.510 (13.0)	21	1.135 (28.8)	58	.898 (22.8)
		16	.570 (14.5)	22	1.210 (30.7)	60	1.023 (26.0)
		17	.635 (16.1)	23	1.275 (32.4)	64	1.137 (28.9)
		18	.695 (17.7)	24	1.380 (35.1)	68	1.357 (34.5)
		27	.766 (19.5)	30	1.380 (35.1)		
		31	.820 (20.8)	25	1.530 (38.9)		